

Protech Graffiti Plus

Semi-permanent anti-graffiti protection for masonry and urban buildings



Protech Graffiti Plus is a ready-to-use transparent, water-based product formulated to protect buildings from vandalism and graffiti. With its special composition, Protech Graffiti Plus creates a barrier that prevents the dye from penetrating the material, maintaining the original breathability of the treated surface. This semi-permanent product can be washed up to 5-6 times before being re-applied.

CUSTOMS CODE: 3824 9970 COMPONENTS: Single-component

APPEARANCE: Liquid

AVAILABLE COLORS: Milky white

PACKAGING AND DIMENSIONS: Plastic can 25 kg

FIELDS OF APPLICATION

Removal of graffiti from the façades of buildings and monuments as well as all civil and industrial buildings.

ALLOWED SUPPORTS

Plasters - Concrete - Prefabricated concrete - Bricks - Paint - Natural stones

PREPARATION OF SUPPORTS

The supports must be dry, clean and dust-free.

MODE OF USE

Protech Graffiti Plus can be applied with rollers or brushes or using airless sprayers until it is no longer absorbed. Generally, a single application of the product is enough to achieve a positive result. If a second application is required for particularly absorbent media, apply the product wet-on-wet. To remove graffiti, clean the surface with Consilex Smog Remover. Allow the product to work its magic then proceed with cleaning the substrate with hot pressurised water. It is possible to clean approximately 5–6 times before having to reapply Protech Graffiti Plus.

APPLICATION METHODS

Low pressure airless nebulizer - Brush - Paint roller



TOOL CLEANING

Water

KEY FEATURES

Shelf-life: 12 months



Temperature of use: +5 / +35 °C



Use wearing protective gloves



Solvent-free



Use wearing protective glasses

TECHNICAL SPECIFICATIONS

pH 6-8

CONSUMPTION

Approximately 0.10 kilogram of Protech Graffiti Plus per square metre of surface to be treated.

STORAGE AND CONSERVATION

Protect from freezing. Store the product in its original packing, in a fresh and dry environment, avoiding frost and direct sunlight. Inadequate storage of the product may result in a loss of rheological performance. Store the product at a temperature between +5°C and +35°C.

PHOTO GALLERY







ADDITIONAL CONTENT



WARNINGS AND PRECAUTIONS

The general information, along with any instructions and recommendations for use of this product, including in this data sheet and eventually provided verbally or in writing, correspond to the present state of our scientific and practical knowledge. Any technical and performance data reported is the result of laboratory tests conducted in a controlled environment and thus may be subject to modification in relation to the actual conditions of implementation.

Azichem Srl does not assume any liability arising from inadequate characteristics related to improper use of the product or connected to defects arising from factors or elements unrelated to the quality of the product, including improper storage. Those wishing to utilise the product are required to determine prior to use whether or not the same is suitable for the intended use, assuming all consequent responsibility.

The technical and characteristic details contained in this data sheet shall be updated periodically. For consultation in real time, please visit the website: www.azichem.com. The date of revision is indicated in the space to the side. The current edition cancels out and replaces any previous version.

Please note that the user is required to read the latest Safety Data Sheet for this product, containing chemical-physical and toxicological data, risk phrases and other information regarding the safe transport, use and disposal of the product and its packaging. For consultation, please visit: www.azichem.com.

It is forbidden to dispose of the product and/or packaging in the environment.

