

Syntech HAG Iniettore

"Flat head" injectors in steel and rubber for masonry injections



This rubber and steel injectors are to be inserted in line with the damage, cracks, loose foundations, joints, cavities and so on, then waterproofed through the use of Syntech HAG Eco and Syntech HAG Flex hydro-expansive polyurethane resins, specifically for immediately stopping water infiltration. Equipped with a "flat head" with non-return valve, it is used in conjunction with the Syntech HAG Connettore. Available in two different sizes: Syntech HAG Iniettore 120 = 120x13 mm; Syntech HAG Iniettore 170 = 170x16 mm.

CUSTOMS CODE: 8481 3091

COMPONENTS: Single-component

APPEARANCE: Mechanical device

AVAILABLE COLORS: Steel

PACKAGING AND DIMENSIONS: Bulk material 120 mm - Bulk material 170 mm

FIELDS OF APPLICATION

Stop the infiltration of pressurised water in buildings by targeted injection of hydro-expansive polyurethane resins SYNTECH H.A.G. or fluid epoxy resins (Syntech IC 55).

ALLOWED SUPPORTS

Concrete - Prefabricated concrete - Bricks - Tuff - Mixed walls (bricks and stones) - Stone walls - Rock walls

PREPARATION OF SUPPORTS

The surfaces of application should be clean and free of any soiling, crumbling and non-adhering parts, powder, mosses, moulds, etc... Drill holes at the predetermined injection points. The injection holes will first be made with a drill bit, which should reached the required and intended depth within the wall body. Subsequently, only for the last superficial 10 cm, a second drilling will be performed in the same hole, with a drill bit bigger to create the seat where the rubber tip of the injector will be inserted.

MODE OF USE

Insert SYNTECH H.A.G. INIETTORE in the intended holes. Screw the end portion of the injector with a suitable key. Screwing the injector will compress the rubber located on its tip, making it swell and thus creating the required mechanical and hydraulic seal. If using an electric screwdriver, do not use it in percussion mode and proceed slowly and without exaggerating when screwing in the injector to avoid breaking it. At this point, the injector is ready to be used. Ensure the seal of the injectors placed in the supports is secure. Given the high injection pressures reached by the pumps, in the case of injectors not positioned securely and correctly there is a real risk that they might come out at high speed from their seat (with the risk of injury to the operators!). Carefully study the positioning of the injectors near the masonry discontinuities to be injected. Bad positioning, too close to the crack to be filled, can cause the breaking of the support itself under the pressure of the pump.

APPLICATION METHODS

Apply by hand - Drill

TOOL CLEANING

Nitro thinner

CONSUMPTION

Product to buy as needed (about 4 pieces per metre on regular cracks).

PHOTO GALLERY



ADDITIONAL CONTENT



WARNINGS AND PRECAUTIONS

The general information, along with any instructions and recommendations for use of this product, including in this data sheet and eventually provided verbally or in writing, correspond to the present state of our scientific and practical knowledge. Any technical and performance data reported is the result of laboratory tests conducted in a controlled environment and thus may be subject to modification in relation to the actual conditions of implementation.

Azichem Srl does not assume any liability arising from inadequate characteristics related to improper use of the product or connected to defects arising from factors or elements unrelated to the quality of the product, including improper storage. Those wishing to utilise the product are required to determine prior to use whether or not the same is suitable for the intended use, assuming all consequent responsibility.

The technical and characteristic details contained in this data sheet shall be updated periodically. For consultation in real time, please visit the website: www.azichem.com. The date of revision is indicated in the space to the side. The current edition cancels out and replaces any previous version.

Please note that the user is required to read the latest Safety Data Sheet for this product, containing chemical-physical and toxicological data, risk phrases and other information regarding the safe transport, use and disposal of the product and its packaging. For consultation, please visit: www.azichem.com.

It is forbidden to dispose of the product and/or packaging in the environment.



Produced and distributed by **AZICHEM srl**
Via Giovanni Gentile, 16/A - 46044 Goito (MN), Italy
Tel: +39 0376.604185 / 604365
Fax: +39 0376 604398
www.azichem.com - info@azichem.com

Update of **07-01-2025**
Terms of sale and legal notices available at
<https://www.azichem.com/general-sales-conditions>
Total pages of this document: 2