

# **Syntech Primer Eposol**



CUSTOMS CODE:

COMPONENTS: Two-components APPEARANCE: Liquid + Liquid AVAILABLE COLORS: Gray

PACKAGING AND DIMENSIONS: Can 4.3 kg [A] - Can 8.6 kg [A] - Can 0.7 kg [B] - Can 1.4 kg [B] - Kit: 1 Can 4.3 kg [A] + 1 Can 0.7 kg [B] - Kit: 1 Can 8.6 kg [A] + 1 Can 1.4 kg [B]

## **ALLOWED SUPPORTS**

Concrete - Metal surfaces - Tiles - Steel - Resin coatings

### **APPLICATION METHODS**

Low pressure airless nebulizer - Brush - Paint roller

#### **TOOL CLEANING**

Syntech Diluente Epoxy

#### **KEY FEATURES**

(C)

Shelf-life: 12 months



Use wearing protective glasses



Temperature of use: +8°C / +30°C °C



Use wearing protective gloves



#### **TECHNICAL SPECIFICATIONS**

in peso Dry residue **72** %

Working temperature -20/+70 °C

ASTM D 4541 Concrete adhesion (direct traction) > 3.5 MPa

Dust-free time at 20°C 4 h

Persoz EN ISO 1522 Hardness **195 s**  EN ISO 2409 Adhesion to substrate **Livello 0** Brookfield EN ISO 2555 Viscosity **2900 cP** 

Complete hardening at 20°C 7 day

a +20°C e 65% di U.R. Touch hardening at 20°C **5-6 h** 

#### STORAGE AND CONSERVATION

Protect from freezing. Store the product in its original packing, in a fresh and dry environment, avoiding frost and direct sunlight. Inadequate storage of the product may result in a loss of rheological performance. Protect from humidity. Store the product at a temperature between +5°C and +35°C.

#### WARNINGS AND PRECAUTIONS

The general information, along with any instructions and recommendations for use of this product, including in this data sheet and eventually provided verbally or in writing, correspond to the present state of our scientific and practical knowledge. Any technical and performance data reported is the result of laboratory tests conducted in a controlled environment and thus may be subject to modification in relation to the actual conditions of implementation.

Azichem Srl does not assume any liability arising from inadequate characteristics related to improper use of the product or connected to defects arising from factors or elements unrelated to the quality of the product, including improper storage. Those wishing to utilise the product are required to determine prior to use whether or not the same is suitable for the intended use, assuming all consequent responsibility.

The technical and characteristic details contained in this data sheet shall be updated periodically. For consultation in real time, please visit the website: www.azichem.com. The date of revision is indicated in the space to the side. The current edition cancels out and replaces any previous version.

Please note that the user is required to read the latest Safety Data Sheet for this product, containing chemical-physical and toxicological data, risk phrases and other information regarding the safe transport, use and disposal of the product and its packaging. For consultation, please visit: www.azichem.com.

It is forbidden to dispose of the product and/or packaging in the environment.

