according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: SYNTECH IC 55 Comp. A

Revision date: 07.08.2019 **Version:** 1.0.0

Print date : 07.08.2019

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

SYNTECH IC 55 Comp. A

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses

Preparation for building and construction: Pure epoxy binder, free of mineral charges and solvents, for consolidation injections. Component A

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

AZICHEM Srl

Street: Via G. Gentile16/A

Postal code/city: 46044 Goito (MN) **Telephone:** +390376604185/604365

Telefax: +39 0376 604398

Information contact: info@azichem.com

1.4 Emergency telephone number

Centro Antiveleni di Milano 02 66101029 (CAV Ospedale Niguarda Ca' Granda -Milano) (24h)

Centro Antiveleni di Pavia 0382 24444 (CAV IRCCS Fondazione Maugeri - Pavia) Centro Antiveleni di Bergamo 800 883300 (CAV Ospedali Riuniti - Bergamo) Centro Antiveleni di Firenze 055 7947819 (CAV Ospedale Careggi - Firenze) Centro Antiveleni di Roma 06 3054343 (CAV Policlinico Gemelli - Roma)

Centro Antiveleni di Roma 06 49978000 (CAV Policlinico Umberto I - Roma) Centro Antiveleni di Napoli 081 7472870

(CAV Ospedale Cardarelli - Napoli)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Aquatic Chronic 2; H411 - Hazardous to the aquatic environment: Chronic 2; Toxic to aquatic life with long lasting effects

Eye Irrit. 2; H319 - Serious eye damage/eye irritation: Category 2; Causes serious eye irritation.

Skin Irrit. 2; H315 - Skin corrosion/irritation: Category 2; Causes skin irritation.

Skin Sens. 1; H317 - Skin sensitisation: Category 1; May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms





Environment (GHS09) · Exclamation mark (GHS07)

Signal word

Warning

Hazard components for labelling

REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700); CAS No.: 25068-38-6

Page: 1/9

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : SYNTECH IC 55 Comp. A

Revision date: 07.08.2019 **Version:** 1.0.0

Print date : 07.08.2019

OXIRANE, MONO[(C12-14-ALKYLOXY)METHYL] DERVIVS; CAS No.: 68609-97-2

Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P302+P352 IF ON SKIN: Wash with plenty of water/....

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P501 Dispose of contents/container in accordance with local regulation

Special rules for supplemental label elements for certain mixtures

EUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3 Other hazards

None

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700)

; CAS No.: 25068-38-6

Weight fraction : \geq 65 - < 70 %

Classification 1272/2008 [CLP] : Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317 Eye Irrit. 2 ; H319 Aquatic Chronic 2 ; H411

OXIRANE, MONO[(C12-14-ALKYLOXY)METHYL] DERVIVS; EC No.: 271-846-8; CAS No.: 68609-97-2

Weight fraction : $\geq 10 - < 15 \%$

Classification 1272/2008 [CLP]: Skin Irrit. 2; H315 Skin Sens. 1; H317

Additional information

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

When in doubt or if symptoms are observed, get medical advice.

Following inhalation

Remove victim out of the danger area. Symptoms may develop several hours following exposure; medical observation therefore necessary for at least 48 hours.

In case of skin contact

Wash immediately with: Water Remove contaminated, saturated clothing immediately. In case of skin irritation, consult a physician. In case of skin reactions, consult a physician.

After eye contact

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Never give anything by mouth to an unconscious person or a person with cramps.

Page: 2/9

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: SYNTECH IC 55 Comp. A

Revision date: 07.08.2019 **Version:** 1.0.0

Print date : 07.08.2019

4.2 Most important symptoms and effects, both acute and delayed

Irritation to eyes May cause an allergic skin reaction. Primary irritation to the skin

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Extinguishing powder alcohol resistant foam Carbon dioxide (CO2) Water mist

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Carbon monoxide.

5.3 Advice for firefighters

Remove persons to safety.

Special protective equipment for firefighters

Do not inhale explosion and combustion gases. Use appropriate respiratory protection.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Clear spills immediately. Wear a self-contained breathing apparatus and chemical protective clothing.

For non-emergency personnel

Remove persons to safety.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3 Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal.

For cleaning up

The contaminated area should be cleaned up immediately with: Water Retain contaminated washing water and dispose it.

6.4 Reference to other sections

Reference to other sections Safe handling: see section 7 Personal protection equipment: see section 8

SECTION 7: Handling and storage



7.1 Precautions for safe handling

Protective measures

Specific requirements or handling rules

Do not breathe dust. Do not breathe gas/fumes/vapour/spray. See section 8.

Advices on general occupational hygiene

Page: 3 / 9

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: SYNTECH IC 55 Comp. A

Revision date : 07.08.2019 **Version :** 1.0.0

Print date : 07.08.2019

Normal precautions taken when handling chemicals should be observed.

7.2 Conditions for safe storage, including any incompatibilities

Only use containers specifically approved for the substance/product.

Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place. Protect against UV-radiation/sunlight Humidity.

Hints on joint storage

Storage class: 10

Storage class (TRGS 510): 10

Keep away from

Store at least 3 metres apart from: Chemicals/products that react together readily

Further information on storage conditions

Keep container tightly closed and in a well-ventilated place.

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

None

8.2 Exposure controls

Appropriate engineering controls

If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Personal protection equipment







When using do not eat, drink, smoke, sniff.

Eye/face protection

Suitable eye protection

Safety glasses with side shields (EN 166).

Skin protection

Hand protection

Wear rubber gloves approved under standard EN374.

Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values

Suitable respiratory protection apparatus

Full-/half-/quarter-face masks (DIN EN 136/140) Filter type: A

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties Safety relevant basis data

Aspect liquid
Colour Straw
Odour none
Melting point/melting range: (1013 hPa) not applicable
Vapour density ((air = 1)) Data not available

Page: 4/9

(EN/D)

according to Regulation (EC) No. 1907/2006 (REACH)



°C

°C

°C

SYNTECH IC 55 Comp. A Trade name:

Revision date: 07.08.2019 Version: 1.0.0

Print date: 07.08.2019

> Initial boiling point and boiling (1013 hPa) 177 range: 210 **Decomposition temperature:** Flash point: 177 Ignition temperature: not applicable Flammability (solid, gas) Data not available Lower explosion limit: No data available Upper explosion limit: No data available Product is not explosive

Explosive properties

(20°C) Vapour pressure No data available (20°C) Density: g/cm3 1.1

Density: (23°C) No data available (20°C) Water solubility: insoluble Soluble in: (20°C) organic solvents pH: No data available Log Pow (20°C) not applicable

Viscosity: (20°C) 1000 mPa.s

Odour threshold Data not available **Evaporation rate** Data not available **Oxidizing properties** Not oxidising

9.2 Other information

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

Decomposes on heating. See section 7. No additional measures necessary.

10.3 Possibility of hazardous reactions

None particular

10.4 Conditions to avoid

Do not expose this product to high temperatures.

10.5 Incompatible materials

May react violently with strong acids. Oxidizing agents. Strong bases.

10.6 Hazardous decomposition products

Carbon monoxide.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute effects

Acute oral toxicity

Parameter: LD50 (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN

(NUMBER AVERAGE MOLECULAR WEIGHT <= 700); CAS No.: 25068-38-6)

Oral Exposure route: Species: Rat

Effective dose: > 2000 mg/kg

Acute dermal toxicity

LD50 (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN Parameter:

(NUMBER AVERAGE MOLECULAR WEIGHT <= 700); CAS No.: 25068-38-6)

Exposure route: Dermal

Page: 5 / 9

(EN/D)

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: SYNTECH IC 55 Comp. A

Revision date: 07.08.2019 **Version:** 1.0.0

Print date : 07.08.2019

Species: Rat

Effective dose: > 2000 mg/kg

Irritant and corrosive effects

Primary irritation to the skin

Irritant.

Irritation to eyes

Irritant.

Irritation to respiratory tract

Not an irritant.

Sensitisation

In case of skin contact

sensitising.

In case of inhalation

not sensitising.

Repeated dose toxicity (subacute, subchronic, chronic)

There were no chronic effects or effects at low concentrations.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

This substance does not meet the criteria for classification as CMR category according to CLP.

SECTION 12: Ecological information

Do not allow uncontrolled discharge of product into the environment.

12.1 Toxicity

Aquatic toxicity

Acute (short-term) fish toxicity

Parameter: LC50 (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN

(NUMBER AVERAGE MOLECULAR WEIGHT <= 700); CAS No.: 25068-38-6)

Species: Oncorhynchus mykiss (Rainbow trout)

Effective dose : 1,2 mg/l Exposure time : 96 h

Acute (short-term) daphnia toxicity

Parameter: EC50 (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN

(NUMBER AVERAGE MOLECULAR WEIGHT <= 700); CAS No. : 25068-38-6)

Species: Daphnia magna (Big water flea)

Effective dose : 2,8 mg/l Exposure time : 48 h

Acute (short-term) algae toxicity

Parameter: EC50 (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN

(NUMBER AVERAGE MOLECULAR WEIGHT <= 700); CAS No. : 25068-38-6)

Species: Selenastrum capricornutum

Effective dose : 9,4 mg/l Exposure time : 9,4 mg/l

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

No information available.

Page: 6 / 9

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: SYNTECH IC 55 Comp. A

Revision date: 07.08.2019 **Version:** 1.0.0

Print date: 07.08.2019

12.6 Other adverse effects

No information available.

12.7 Additional ecotoxicological information

None

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product/Packaging disposal

Dispose according to legislation.

SECTION 14: Transport information

14.1 UN number

UN 3082

14.2 UN proper shipping name

Land transport (ADR/RID)

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700))

Sea transport (IMDG)

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700))

Air transport (ICAO-TI / IATA-DGR)

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (REACTION PRODUCT: BISPHENOL A-(EPICHLORHYDRIN), EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT <= 700))

14.3 Transport hazard class(es)

Land transport (ADR/RID)

Class(es): 9
Classification code: M6
Hazard identification number (Kemler
No.): 90

Tunnel restriction code : E

Special provisions : LQ $5 \cdot E \cdot 1 \cdot ADR : -(SP \cdot 375 \le 5 \cdot 1/kg)$

Hazard label(s): 9 / N

Sea transport (IMDG)

Class(es): 9 **EmS-No.:** F-A / S-F

Special provisions : LQ $5 \mid \cdot \mid E \mid 1 \cdot \mid MDG : -(SP 2.10.2.7 <= 5 \mid /kg)$

Hazard label(s): 9 / N

Air transport (ICAO-TI / IATA-DGR)

Class(es):

Special provisions : E 1 · IATA : - (SP A197 \leq 5 l/kg)

Hazard label(s): 9 / N

14.4 Packing group

Ш

14.5 Environmental hazards

Land transport (ADR/RID): Yes **Sea transport (IMDG):** Yes (P)

Air transport (ICAO-TI / IATA-DGR): Yes

14.6 Special precautions for user

Page: 7 / 9

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: SYNTECH IC 55 Comp. A

Revision date: 07.08.2019 **Version:** 1.0.0

Print date: 07.08.2019

None

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture $^{15.1}$

EU legislation

Regulation (EC) 1907/2006 (REACh). Regulation (EC) No 1272/2008 (CLP).

Regulation (EU) 2015/830 requirements for the compilation of safety data sheets.

Amendings, for the purposes of its adaptation to technical and scientific progress, Regulation (EC) No 1272/2008: Commission Regulation (EC) No 790/2009 (I ATP). Commission Regulation (EU) No 286/2011(II ATP). Commission Regulation (EU) No 618/2012 (III ATP). Commission Regulation (EU) No 487/2013 (IV ATP). Commission Regulation (EU) No 944/2013 (V ATP). Commission Regulation (EU) No 605/2014 (VI ATP). Commission Regulation (EU) No 1297/2014 (VII ATP). Commission Regulation (EU) No 2015/1221 (VIII ATP). Commission Regulation (EU) No 2016/1179 (IX ATP). Commission Regulation 2017/776 (EU) No (X ATP).

Other regulations (EU)

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive] Classification according to Annex I, Part 1 E2 Hazardous to the aquatic environment in Category Chronic 2

Regulation (CE) 1907/2006: Substance of very high concern included in the SVHC Candidate List None

National regulations

Italy: Legislative Decree 81/2008 (Consolidated Law on protection of health and safety at work), as amended and Directive 2009/161/UE - chemical risk assessment in accordance with Title IX

Water hazard class (WGK)

Class: 2 (Hazardous to water) Classification according to VwVwS

15.2 Chemical safety assessment

not applicable

SECTION 16: Other information

16.1 Indication of changes

None

16.2 Abbreviations and acronyms

LEGENDA:

ADR: Accord européen relative au transport international des marchandises dangereuses par route (accordo

europeo relativo al trasporto internazionale delle merci pericolose su strada)

ASTM: ASTM International, originariamente nota come American Society for Testing and Materials (ASTM)

EINECS: European Inventory of Existing Commercial Chemical Substances (Registro Europeo delle Sostanze

chimiche in Commercio)

EC(0/50/100): Effective Concentration 0/50/100 (Concentrazione Effettiva Massima per 0/50100% degli Individui)

LC(0/50/100): Lethal Concentration 0/50/100 (Concentrazione Letale per 0/50100% degli Individui)

IC50: Inhibitor Concentration 50 (Concentrazione Inibente per il 50% degli Individui)

NOEL: No Observed Effect Level (Dose massima senza effetti)

NOEC: No Observed Effect Concentration (Concentrazione massima senza effetti)

LOEC: Lowest Observed Effect Concentration (Concentrazione massima alla quale è possibile evidenziare un

effetto)

DNEL: Derived No Effect Level (Dose derivata di non effetto)

DMEL: Derived Minimum Effect Level (Dose derivata di minimo effetto)

CLP: Classification, Labelling and Packaging (Classificazione, Etichettatura e Imballaggio)

CSR: Rapporto sulla Sicurezza Chimica (Chemical Safety Report)

Page: 8 / 9

(EN/D)

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: SYNTECH IC 55 Comp. A

Revision date: 07.08.2019 **Version:** 1.0.0

Print date: 07.08.2019

LD(0/50/100): Lethal Dose 0/50/100 (Dose Letale per 0/50/100% degli Individui)

IATA: International Air Transport Association (Associazione Internazionale del Trasporto Aereo)

ICAO: International Civil Aviation Organizzation (Organizzazione Internazionale dell'Aviazione Civile)

Codice IMDG: International Maritime Dangerous Goods code (Codice sul Regolamento del Trasporto Marittimo)

PBT: Persistent, bioaccumulative and toxic (sostanze persistenti bioaccumulabili e tossiche)

RiD: Règlement concernent le transport International ferroviaire des marchandises Dangereuses (Regolamento concernente il trasporto Internazionale ferroviario delle merci Pericolose)

STEL: Short term exposure limit (limite di esposizione a breve termine)

TLV: Threshold limit value (soglia di valore limite)

TWA: Time Weighted Average (media ponderata nel tempo)

UE: Unione Europea

vPvB: Very persistent very bioaccumulative (sostanze molto persistenti e molto bioaccumulabili)

N.D.: Non disponibile. N.A.: Non applicabile

AwSV.: Ordinance on facilities for handling substances that are hazardous to water (Verordnung über Anlagen

zum Umgang mit wassergefährdenden Stoffen (AwSV))

PNEC: Predicted No Effect Concentration
PNOS: Particulates not Otherwise Specified
BOD: Biochemical Oxygen Demand
COD: Chemical Oxygen Demand
BCF: BioConcentration Factor

TRGS: Technische Regeln für Gefahrstoffe -Technical Rules for Hazardous Substances, defined by The

Federal Institute for Occupational Safety and Health, Germany

LCLo: Lethal Concentration Low (La minima concentrazione letale)

ThOD: Theoretical Oxygen Demand

16.3 Key literature references and sources for data

None

$^{16.4}$ Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

calculated.

16.5 Relevant H- and EUH-phrases (Number and full text)

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Page: 9/9